

TSXRKY8

non-extendable rack - for single rack configuration - 8 slots - IP20

Main

Range of product	Modicon Premium Automation platform
Product or component type	Non-extendable rack
Product specific application	For single rack configuration

Complementary

Number of slots	8
Product compatibility	I/O module Specific application module TSXP57 processor TSXPSY power supply
Fixing mode	By 4 M6 screws panel By clips 35 mm symmetrical DIN rail
Marking	CE
Product weight	1.75 kg

Environment

Standards	73/23/EEC 73/23/EEC 73/23/EEC 73/23/EEC 73/23/EEC 89/336/EEC 89/336/EEC 89/336/EEC 89/336/EEC 89/336/EEC 92/31/EEC 92/31/EEC 92/31/EEC 92/31/EEC 92/31/EEC 92/31/EEC 93/68/EEC 93/68/EEC 93/68/EEC 93/68/EEC 93/68/EEC CSA C22.2 No 142 CSA C22.2 No 142 CSA C22.2 No 142 CSA C22.2 No 142 CSA C22.2 No 142 IEC 61131-2 IEC 61131-2 IEC 61131-2 IEC 61131-2 IEC 61131-2 UL 508 UL 508 UL 508 UL 508 UL 508 CSA C22.2 No 213 Class I Division 2 Group A CSA C22.2 No 213 Class I Division 2 Group A CSA C22.2 No 213 Class I Division 2 Group A CSA C22.2 No 213 Class I Division 2 Group A CSA C22.2 No 213 Class I Division 2 Group A CSA C22.2 No 213 Class I Division 2 Group B CSA C22.2 No 213 Class I Division 2 Group B CSA C22.2 No 213 Class I Division 2 Group B CSA C22.2 No 213 Class I Division 2 Group B CSA C22.2 No 213 Class I Division 2 Group B CSA C22.2 No 213 Class I Division 2 Group B CSA C22.2 No 213 Class I Division 2 Group B CSA C22.2 No 213 Class I Division 2 Group B CSA C22.2 No 213 Class I Division 2 Group C
-----------	---

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

CSA C22.2 No 213 Class I Division 2 Group C
 CSA C22.2 No 213 Class I Division 2 Group C
 CSA C22.2 No 213 Class I Division 2 Group C
 CSA C22.2 No 213 Class I Division 2 Group C
 CSA C22.2 No 213 Class I Division 2 Group D
 CSA C22.2 No 213 Class I Division 2 Group D
 CSA C22.2 No 213 Class I Division 2 Group D
 CSA C22.2 No 213 Class I Division 2 Group D
 CSA C22.2 No 213 Class I Division 2 Group D

Product certifications	ABS BV DNV GL LR RINA RMRS
Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-25...70 °C
Relative humidity	10...95 % without condensation for operation 5...95 % without condensation for storage
Operating altitude	0...2000 m
Protective treatment	TC
IP degree of protection	IP20
Pollution degree	2

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Will not be Compliant
REACH	Reference not containing SVHC above the threshold