

# TSXASZ200

TSX Micro - 2 analogue output +/- 10 V, 0-20, 4-20 mA



## Main

Range of product	Modicon TSX Micro automation platform
Product or component type	Analog output module
Number of channels	2
Analogue output type	+/- 10 V 0...20 mA or 4...20 mA

## Complementary

Analog/digital conversion	11 bits + sign 0...20 mA or 4...20 mA 11 bits +/- 10 V
Measurement resolution	0...20 mA or 4...20 mA +/- 10 V
Output load	<= 0.6 Ohm 0...20 mA or 4...20 mA >= 1 Ohm +/- 10 V
Protection type	Open-circuit 0...20 mA or 4...20 mA
Temperature drift	0.107 %/10 °C 0...20 mA or 4...20 mA 0.083 %/10 °C +/- 10 V
Current consumption	150 mA
Isolation voltage	1500 V AC
Product weight	0.2 kg

## Environment

## Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Will not be Compliant

## Wiring Diagram

Channel 0 output voltage	①	②	Shared channels
Shielding connection	③	④	Shielding connection
Channel 0 output current	⑤	⑥	Shared channels
Shielding connection	⑦	⑧	Shielding connection
Channel 1 output voltage	⑨	⑩	Shared channels
Shielding connection	⑪	⑫	Shielding connection
Channel 1 output current	⑬	⑭	Shared channels
Shielding connection	⑮		

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.