140CRP93200

RIO head-end adaptor module Modicon Quantum - 2 connectors with redundant cable





Main

Range of product	Modicon Quantum automation platform
Product or component type	RIO head-end adaptor module

Complementary

Product compatibility	Quantum 200/500/800 series Symax (any mix)	
Drops/network	<= 31	
I/O words/drop	64 I/64 O	
Type of cable	Coaxial 75 Ohm	
Transmission rate	1544 Mbit/s	
Dynamic range	35 dB	
Isolation voltage	500 V DC coaxial center and ground	
Electrical connection	2 female connectors F elbowed with redundant cable	
Diagnostics startup	LAN controller check Memory check Power up	
Power dissipation in W	3 W 2 channels	
Marking	CE	
Bus current requirement	750 mA 2 channels	
Module format	Standard	

Environment

Product certifications	FM Class 1 Division 2	
Standards	CSA C22.2 No 142 CUL UL 508	
Resistance to electrostatic discharge	4 kV contact conforming to IEC 801-2 8 kV on air conforming to IEC 801-2	
Resistance to electromagnetic fields	10 V/m 801000 MHz conforming to IEC 801-3	
Ambient air temperature for operation	00° °C	
Ambient air temperature for storage	-4085 °C	
Relative humidity	95 % without condensation	
Operating altitude	<= 5000 m	

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS	Compliant - since 0901 - Schneider Electric declaration of conformity	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	

