



Facts

General description

Part number	630005305
Part status	Active
Warranty	2 year

Certifications

General	CE, FCC, KCC, UL 61010-2-201
---------	------------------------------

Mechanical

Mechanical size	284 x 187 x 52mm
Mounting option	Panel Mount
Number of touches	1million finger touch operations
Touch type	Resistive
Cut-out size	275 x 177
Weight	1.3 kg
Housing material	Plastic (PC+ABS), Gray

Power

Input voltage	24 V DC (18 to 32 VDC)CE: The power supply must conform with the requirements according to IEC 60950 and IEC 61558-2-4.UL and cUL: The power supply must conform with the requirements for class II power supplies.
---------------	---

Power consumption (max)	10.8W
Input fuse	Internal DC fuse

System

CPU	ARM9 400 MHz
RAM	128 MB
FLASH	256 MB, 200 MB free

X2 base 10

10" HMI with iX runtime

800 x 480 pixel (16:9)
 TFT-LCD touch screen
 200 MB application memory
 1 x Ethernet, 4 x serial, 1 x USB as standard
 Operating temperature -10° to +50° C
 CE, FCC, KCC, UL approvals

Display

Size diagonal	10.1" diagonal
Resolution	800x480 pixels
Backlight	LED Backlight
Backlight life time	20000 hours
Backlight brightness	350 cd/m²
Backlight dimming	Industrial Dimming
Display type	TFT-LCD with LED backlight

Communication serial

Number of serial ports	2 Port 9pin DSUB
Serial port 1	RS 232 (RTS/CTS)
Serial port 2	RS422/485
Serial port 3	RS 232
Serial port 4	RS 485

Ethernet communication

Number of ethernet ports	1
Ethernet port 1	1x10/100 Base-T (shielded RJ45)

Expansion interface

Expansion port	No
SD card	No
USB	1xUSB 2.0 400mA

Environmental

Operating temperature	-10°C to +50°C
Storage temperature	-20° to +60°C
Shock	15g, half-sine, 11ms according to IEC60068-2-27
Vibration	1g, according to IEC 60068-2-6, Test Fc
Sealing front	IP65
Sealing back	IP20
Humidity	5% – 85% non-condensed