



**Facts**

**General description**

Part number	640009505
Part status	Active
Warranty	2 year

**Certifications**

General	CE, UL 61010-2-201, FCC
---------	-------------------------

**Mechanical**

Mechanical size	556 x 347 x 65mm
Mounting option	Panel Mount, VESA 75 x 75
Number of touches	1million finger touch operations
Touch type	Resistive
Cut-out size	539 x 331mm
Weight	7.38 kg
Housing material	Powder-coated aluminum, Gray

**Power**

Input voltage	24 V DC (18 to 32 VDC) CE: The power supply must conform with the requirements according to IEC 60950 and IEC 61558-2-4. UL and cUL: The power supply must conform with the requirements for class II power supplies.
---------------	---

Power consumption (max)	45.6W
Input fuse	Internal DC fuse

**System**

CPU	i.MX6Quad, Quad ARM Cortex-A9 1.0GHz 1MB L2 cache
RAM	2 GB
FLASH	2GB SSD(eMMC), 1.5GB free for application

**Display**

Size diagonal	21.5" diagonal
Resolution	1920x1080 pixels
Backlight	LED Backlight
Backlight life time	50000 hours
Backlight brightness	250 cd/m <sup>2</sup>
Backlight dimming	Industrial Dimming
Display type	TFT-LCD with LED backlight

**X2 pro 21**

**21" HMI with iX software**

Full 1920 × 1080 pixel HD resolution (16:9)  
TFT-LCD touch screen  
1.5 GB application memory  
Ethernet 2x100 Mbit  
0°C to +50°C operating temperature  
CE, FCC, UL approvals

**Digital IO**

Digital output	2xDO Solid state relay, 0.5A@24VDC
----------------	------------------------------------

**Communication serial**

Number of serial ports	1 Port 9pin DSUB
Serial port 1	RS 232 (RTS/CTS)
Serial port 2	RS422/485
Serial port 3	RS485 (only if COM 2 is RS485)

**Ethernet communication**

Number of ethernet ports	2
Ethernet port 1	1x10/100 Base-T (shielded RJ45)
Ethernet port 2	1x10/100 Base-T (shielded RJ45)

**Expansion interface**

Expansion port	Yes, ciX expansion module
SD card	SD and SDHC
USB	2xUSB 2.0 500mA

**Environmental**

Operating temperature	0°C to +50°C
Storage temperature	-20°C to +60°C
Shock	15g, half-sine, 11ms according to IEC60068-2-27
Vibration	1g, according to IEC 60068-2-6, Test Fc
Sealing front	IP65, NEMA 4X/ 12 and UL Type 4X/ 12
Sealing back	IP20
Humidity	5% – 85% non-condensed