ZB6AS934

red Ø30 Emergency stop pushbutton head Ø16 trigger and latching key release



Main

Commercial Status	Commercialised
Range of product	Harmony XB6
Product or component type	Head for emergency stop pushbutton
Device short name	ZB6
Bezel material	Plastic
Mounting diameter	16 mm
Sale per indivisible quantity	1
Shape of signaling unit head	Round
Type of operator	Trigger action and mechanical latching
Reset	Key release
Operator profile	Red mushroom Ø 30 mm unmarked
Type of keylock	Ronis 200

Complementary

CAD overall width	30 mm	
CAD overall height	30 mm	
CAD overall depth	70 mm	
Product weight	0.05 kg	
Mechanical durability	100000 cycles	

Environment

Environment	
Protective treatment	TC
Ambient air temperature for storage	-4070 °C
Ambient air temperature for operation	-2570 °C
Class of protection against electric shock	Class II conforming to IEC 61140
IP degree of protection	IP65 conforming to IEC 60529
NEMA degree of protection	NEMA 4X conforming to CSA C22.2 No 94 NEMA 4 conforming to CSA C22.2 No 94 NEMA 13 conforming to CSA C22.2 No 94 NEMA 4X conforming to UL 50 NEMA 4 conforming to UL 50 NEMA 13 conforming to UL 50
Standards	EN/IEC 60204-1 EN/IEC 60947-1 EN/IEC 60947-5-1 EN/IEC 60947-5-5 EN/ISO 13850 JIS C 4520 JIS C 852 UL 508 CSA C22.2 No 14
Product certifications	CCC CSA GOST UL
Vibration resistance	5 gn (f = 2500 Hz) conforming to IEC 60068-2-6 +/- 3 mm (f = 2500 Hz) conforming to IEC 60068-2-6
Shock resistance	Conforming to IEC 60068-2-27 Conforming to IEC 60068-2-27