# XVEC2B5

# ORANGE STEADY LENS INTEGRAL LED 24VAC/DC



#### Main

Range of product	Harmony XVE Optimum
Product or component type	Indicator bank
Beacon or indicator bank unit ty	ypellluminated unit
Signalling type	Steady
Component name	XVE
Light source	Orange integral LED
Bulb type	LED
[Us] rated supply voltage	24 V AC/DC

## Complementary

Mounting diameter	70 mm	
Assembly style	Customer assembly	
Connections - terminals	Screw clamp terminals: <= 1 x 1.5 mm <sup>2</sup> with cable end	_
Marking	CE	
Overld and short-circuit prot	0.63 A	
[Ui] rated insulation voltage	250 V conforming to IEC 60947-1	
Nominal voltage limit	0.851.1 Un conforming to IEC 60947-5-1	
Current consumption	< 25 mA	
[Uimp] rated impulse withstand voltage	4 kV conforming to IEC 60947-1	
Luminance	800 cd/m <sup>2</sup>	
CAD overall width	70 mm	
CAD overall height	52 mm	
CAD overall depth	70 mm	
Product weight	0.077 kg	

## **Environment**

Standards	EN/IEC 60947-1	
	EN/IEC 60947-5-1	
Product certifications	CCC CSA UL	
Ambient air temperature for storage	-4070 °C	
Ambient air temperature for operation	-2555 °C	
Class of protection against electric shock	Class I aluminium tube mounting conforming to IEC 61140 Class I plastic tube mounting conforming to IEC 61140	
Protective treatment	TC	
IP degree of protection	IP40 in any position except vertical position conforming to IEC 60529 IP42 in vertical position conforming to IEC 60529	