

### Main

Commercial Status	Commercialised
Range of product	Harmony XVD Application
Product or component type	Base unit with cover
Component name	XVD
Indicator bank base type	Standard
Material	Polycarbonate cover unit Glass reinforced polyamide base unit

### Complementary

Fixing mode	Direct or tube fixing
Mounting diameter	70 mm
Product destination	Banks without flash discharge tube unit
Cable entry	Bottom entry
Assembly style	Customer assembly, up to 5 units
Terminals description ISO n°1	(COM-1)PW (COM-2)PW (COM-3)PW (COM-4)PW (COM-5)PW (GND)GROUND
Product weight	0.18 kg

### Environment

Product certifications	CSA GOST UL
Standards	EN/IEC 60947-5-1
Protective treatment	TC
Ambient air temperature for storage	-40...70 °C
IP degree of protection	IP40 IEC 60529


### Contractual warranty

Period	18 months
--------	-----------

Customer Assembled Indicator Bank without “Flash” Discharge Tube

Dimensions

Below drawing shows the minimum configuration of the product. Select the number of stages according to the product characteristics in order to get b dimension.



- (1) Base unit
- (2) Illuminated unit XVDC3•/C4•• or audible unit XVDC9•, to be ordered separately
- (3) Cover (included with base unit)

Number of illuminated or audible signalling units (no “flash”)	b in mm	b in in.
1	140	5.51
2	203	7.99
3	266	10.47
4	329	12.95
5	392	15.43

---

Customer Assembled Beacons and Indicator Banks

---

Wiring Diagrams

