



Main

| | |
|-------------------------------|--|
| Range of product | Harmony XVD Optimum |
| Product or component type | Complete miniature beacon |
| Beacon/indicator bk unit type | Base unit with direct fixing mode Illuminated unit |
| Signalling type | Steady |
| Mounting diameter | 45 mm |
| Component name | XVDLS |
| Material | Glass reinforced polyamide (base unit) Polycarbonate (illuminated unit) |
| Light source | Red bulb not included |
| Bulb type | Incandescent with BA 15d |
| [Us] rated supply voltage | <= 230 V |
| Power dissipation in W | < 5 W |

Complementary

| | |
|--|---|
| Connections - terminals | Screw clamp terminals, connection capacity: <= 1 x 1.5 mm ² with cable end |
| Cable entry | 1 entry tapped for Pg 7 |
| [Ui] rated insulation voltage | 250 V conforming to IEC 60947-1 |
| [Uimp] rated impulse withstand voltage | 4 kV conforming to IEC 60947-1 |
| CAD overall width | 45 mm |
| CAD overall height | 104 mm |
| CAD overall depth | 45 mm |
| Terminals description ISO n°1 | (COM-1)PW (GND)GROUND |
| Product weight | 0.08 kg |


Environment

| | |
|--|----------------------------------|
| Product certifications | CSA UL |
| Standards | EN/IEC 60947-5-1 |
| Protective treatment | TC |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...70 °C |
| Class of protection against electric shock | Class II conforming to IEC 60536 |
| IP degree of protection | IP40 conforming to IEC 60529 |

Illuminated Beacon

Dimensions

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.



Illuminated Beacon

Panel Cut-out for Direct Fixing

