XVEC21 BASE UNIT WITH SNAP-ON COVER





Main

| Range of product | Harmony XVE Optimum |
|---------------------------|----------------------|
| Product or component type | Base unit with cover |
| Kit composition | Base unit Cover |
| Component name | XVE |

Complementary

| Mounting diameter | 70 mm |
|-------------------------------|------------------------------------------------------------------------------|
| Assembly style | Customer assembly |
| Marking | CE |
| Terminals description ISO n°1 | (COM-1)PW (COM-2)PW (COM-3)PW (COM-4)PW (COM-5)PW (GND)GROUND |
| Product weight | 0.11 kg |

Environment

| Standards | EN/IEC 60947-1 EN/IEC 60947-5-1 | _ |
|--------------------------------------------|---------------------------------------------------------------------------------------------------------------|---|
| Product certifications | CCC CSA UL | |
| Ambient air temperature for storage | -4070 °C | |
| Ambient air temperature for operation | -2555 °C | |
| Class of protection against electric shock | Class I aluminium tube mounting conforming to IEC 61140 Class I plastic tube mounting conforming to IEC 61140 | |
| Protective treatment | TC | |
| IP degree of protection | IP42 (indoor) conforming to IEC 60529 | |

Indicator Bank

Wiring Diagram

