

XVMC21

base unit with cover XVM - Ø 45 mm - white - screw terminals - IP40



Main

Range of product	Harmony XVM
Product or component type	Base unit with cover
Kit composition	Base unit Cover
Component name	XVM
Indicator bank base type	Base without buzzer

Complementary


Mounting diameter	45 mm
Housing colour	White
Connections - terminals	Screw terminals: 1 x 0.325...1 x 1.5 mm ²
Marking	CE
Product weight	0.055 kg

Environment

Standards	EN/IEC 60947-1 EN/IEC 60947-5-1
Product certifications	CCC
Ambient air temperature for storage	-25...70 °C
Ambient air temperature for operation	-10...50 °C
Class of protection against electric shock	Class I aluminium tube mounting conforming to IEC 60947-1 Class I aluminium tube mounting conforming to IEC 60947-5-1 Class I aluminium tube mounting conforming to IEC 61140
IP degree of protection	IP40 in any position except vertical position conforming to IEC 60529 IP42 in vertical position conforming to IEC 60529
Protective treatment	TC

Customer Assembled Tower Light

Wiring Diagram



Indicator bank with buzzer (4 illuminated units max.):

4: 4th illuminated unit

3: 3rd illuminated unit

2: 2nd illuminated unit

1: 1st illuminated unit

N: Common

B: Buzzer

Indicator bank without buzzer:

5: 5th illuminated unit

4: 4th illuminated unit

3: 3rd illuminated unit

2: 2nd illuminated unit

1: 1st illuminated unit

N: Common

Maximum capacity for wiring through support tube:

- 6 wires x 1 mm²/16 AWG,
- 5 wires x 1.5 mm²/14 AWG