

### Main

Commercial Status	Commercialised
Range of product	Harmony XVP Universal
Product or component type	Base unit with cover
Mounting diameter	50 mm
Component name	XVPC
Housing colour	Black
Connections - terminals	Screw clamp terminals: <= 1 x 1.5 mm <sup>2</sup> with or without cable end

### Complementary

Fixing mode	Direct or tube fixing
Material	Polyamide on cover unit Acrylic butadiene styrene + polycarbonate on base unit
Assembly style	Customer assembly, up to 5 units
Marking	CE
[Ui] rated insulation voltage	250 V conforming to IEC 60947-1
[Uimp] rated impulse withstand voltage	4 kV conforming to IEC 60947-1
Terminals description ISO n°1	(COM-1)PW (COM-2)PW (COM-3)PW (COM-4)PW (COM-5)PW (GND)GROUND
Product weight	0.125 kg

### Environment

Product certifications	CULus
Standards	EN/IEC 60947-5-1
Protective treatment	TC
Ambient air temperature for storage	-40...70 °C

### Contractual warranty


Period	18 months
--------	-----------

---

Base Unit for Indicator Banks

---

Panel Cut-out for Direct Fixing




---

Indicator Bank

---

Wiring Diagram



- +/1 Power supply for first unit
- +/2 Power supply for second unit
- +/3 Power supply for third unit
- +/4 Power supply for fourth unit
- +/5 Power supply for fifth unit
- /C Common for all units