

### Main

Commercial Status	Commercialised
Range of product	Harmony XVR
Product or component type	Prewired rotating mirror beacon
Sound signalling	Without
Device short name	XVR
Mounting diameter	130 mm
IP degree of protection	IP67 conforming to IEC 60529 IP66 conforming to IEC 60529
[Us] rated supply voltage	230 V AC
Light source	High luminosity LED, red

### Complementary

Material	PC (globe) ABS (acrylonitrile butadiene-styrene) (body part)
CAD overall width	130 mm
CAD overall depth	130 mm
Product weight	0.99 kg
Marking	CE
Product mounting	By 3 M6 screws
[Uimp] rated impulse withstand voltage	4 kV
Current consumption	22 mA
Flashing frequency	2.7 Hz
Clamping connection capacity	1.25 mm <sup>2</sup>
AWG gauge	18
Cable length	400 mm

### Environment

Standards	EN/IEC 60947-1 EN/IEC 60947-5-1
Protective treatment	TC
Ambient air temperature for storage	-35...70 °C
Ambient air temperature for operation	-30...50 °C
Class of protection against electric shock	Class II conforming to IEC 61140

### RoHS compliance


RoHS EUR status	Compliant
RoHS EUR conformity date(YYWW)	0808

### Contractual warranty

Period	18 months
--------	-----------

Rotating Mirror Beacon

Dimensions



Rotating Mirror Beacon

Panel Cut-out

