

Main

Commercial Status	Commercialised
Range of product	Harmony XVS
Product or component type	Electronic alarm
Device short name	XVS

Complementary

Colour	White
Material	PC (terminal cover) ABS (acrylonitrile butadiene-styrene) (body)
Product weight	0.18 kg
Marking	CE
Product mounting	DIN72 panel mounting
[Uimp] rated impulse withstand voltage	0.8 kV
Current consumption	200 mA at 24 V 158 mA at 12 V 125 mA at 24 V 117 mA at 12 V
Clamping connection capacity	<= 1 x 1.5 mm ²
Width	72 mm
Height	72 mm
Depth	69.3 mm

Environment

Discrete output type	PNP
Signalling type	16 tones alarm
Standards	EN/IEC 61000-6-2 EN/IEC 61000-6-3 UL 464
Product certifications	UR
Protective treatment	TC
Ambient air temperature for storage	-35...70 °C
Ambient air temperature for operation	-10...50 °C
Class of protection against electric shock	Class II conforming to EN/IEC 61140
IP degree of protection	IP54 conforming to EN/IEC 60529
[Us] rated supply voltage	24 V AC/DC 12 V AC/DC
Noise level	0...90 dB (continuous or intermittent tone) at 1 m

RoHS compliance

RoHS EUR status	Compliant
RoHS EUR conformity date(YYYWW)	0808

Contractual warranty

Period	18 months
--------	-----------

Electronic Alarm

Dimensions

