



### Main

Range	Acti 9
Product name	Acti 9 IsoBar P B
Product or component type	Distribution board
Device application	Distribution
Enclosure type	Standard
Provided equipment	Door Enclosure Earth terminal block Neutral terminal block Earth stud Removable gland plates Blanking plate Front cover Pan assembly
Colour	Cream RAL 9001

### Complementary

Enclosure mounting	Surface
Poles description	3P + N
[Ie] rated operational current	250 A 400/415 V AC 250 A 230/240 V AC
Breaking capacity	25 kA
Overvoltage category	IV
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	6 kV
Incomer device	Switch disconnecter 3P + N Switch disconnecter 4P MCCB 4P Terminal block 4P Contactor 4P RCCB 4P
Protection device type	Miniature circuit breaker (MCB) 63 A max Residual current circuit breaker with overcurrent protection (RCBO) 45 A- max 100 mA max Residual current circuit breaker with overcurrent protection (RCBO PoN) 45 A- max 100 mA max
Number of ways	4 ways as outgoer - 3P
Enclosure material	Steel
Surface treatment	Epoxy
Surface finish	Powder paint
Height	484 mm
Width	470 mm

Depth	139 mm
Product weight	9 kg

### Environment

Standards	BS EN 61439-3
IP degree of protection	IP2x without cover internal BS EN 60529 IP3x with cover external BS EN 60529
IK degree of protection	IK05
Ambient air temperature for operation	-35...70 °C
Ambient air temperature for storage	-40...80 °C

### Offer Sustainability

Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Product Life Status :	<b>Commercialised</b>
-----------------------	-----------------------