



Main

Range of product	PowerPact multistandard
Range	PowerPact
Product name	H-Frame
Device short name	H-Frame
Product or component type	Circuit breaker
Device application	Distribution

Complementary

Poles description	3P
Control type	Toggle
Mounting mode	Unit mount
Mounting support	DIN rail Backplate Flush
Electrical connection	Terminal nut line side Terminal nut load side
[In] rated current	100 A at 40 °C
[Ui] rated insulation voltage	750 V AC at 50/60 Hz conforming to IEC 60947-2
[Uimp] rated impulse withstand voltage	8 kV conforming to IEC 60947-2
[Ue] rated operational voltage	525 V AC at 50/60 Hz conforming to IEC 60947-2 690 V AC at 50/60 Hz conforming to IEC 947-2 600 V AC at 50/60 Hz conforming to UL 489
Breaking capacity code	HD
Suitability for isolation	Yes
Utilisation category	Category A
Mechanical durability	4000 cycles
Electrical durability	4000 cycles
Connection pitch	45 mm
Local signalling	ON/OFF indication

Contact position indicator	Yes
Trip unit name	TM
Trip unit technology	Thermal-magnetic
Trip unit protection functions	Basic protection
Trip unit rating	100 A
Display type	3 LEDs
Breaking capacity	25 kA at 240 V - AC conforming to UL 489 18 kA at 480 V - AC conforming to UL 489 14 kA at 600 V - AC conforming to UL 489 Icu : 25 kA at 220/240 V - AC conforming to IEC 947-2 Icu : 18 kA at 380/415 V - AC conforming to IEC 947-2 Icu : 18 kA at 440/480 V - AC conforming to IEC 947-2 Icu : 14 kA at 500/525 V - AC conforming to IEC 947-2
[Ics] rated service breaking capacity	Ics : 25 kA at 220/240 V - AC conforming to IEC 947-2 Ics : 18 kA at 380/415 V - AC conforming to IEC 947-2 Ics : 18 kA at 440/480 V - AC conforming to IEC 947-2 Ics : 14 kA at 500/525 V - AC conforming to IEC 947-2
Long time pick-up adjustment type Ir	Fixed
Long time pick-up adjustment range	1 In
Short-time pick-up adjustment type I _{sd}	Fixed
[I _{sd}] short-time pick-up adjustment range	1700 A
Overvoltage category	II
Provision for padlocking	Non padlockable
Height	163 mm
Width	104 mm
Depth	86 mm
Standards	W-C-375B/GEN CSA C22.2 No 5 IEC 60947-2 NEMA AB1 NMX J-266 UL 489
Product certifications	CE CCC
Product weight	2.2 kg

Environment

IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 62262
Pollution degree	3 conforming to IEC 60664-1 3 conforming to IEC 60947-1
Ambient air temperature for operation	40 °C
Ambient air temperature for storage	-50...85 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0832 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations