

Product Data Sheet

GW68017N

68 Q-DIN




A complete system of IP65 boards for distributing energy in tertiary, commercial sector and building applications, available both empty and pre-wired, in accordance with the international standard EN 61439-3 and EN 61439-4.. The distribution boards allow to house flush-mounting and interloked socket-outlets up to 63A and versions are available with 5, 10, 14 or 20 DIN modules and addictional modules 14 and 20 DIN modules in order to increase modular space inside the boards.. The switches can always be inspected thanks to the wide transparent door with ergonomic handle and "hinged" screws of the front of board facilitate the wiring and maintenance.. Q-DIN are ideally for fixed applications: surface-mounting or pole-mounting , and transportable application: by handle and carrier.. To ensure the best possible performance even in outdoor environments, prolonged exposure to the sun and bad weather, the boards are also UV resistant certified in compilance with EN62208.

| Colour | Grey RAL 7035 | IP degree | IP65 |
|-------------------------|------------------|---------------------------|-----------------------|
| No. of modules EN 50022 | 5 | Houseable socket | 1 IEC 309 16A IP44/67 |
| Installation type | Surface-mounting | Dispersible power A (W) | 10 |
| Dispersible power B (W) | 37 | Accordance with Standards | EN 62208 |
| Glow Wire Test | 650 °C | Mechanical resistance | IK08 |
| Operating temperature | -25 +40 °C | Thermo-pressure with ball | 70 °C |
| Insulation class | II | Version | Empty |

| BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS | | | | | | | | | | |
|--|--------------------------------------|-----------|--------------|-----------|--------------------------------------|------------------|------------------|-------------------------------------|-------------------------------------|--------------------------------------|
| Saline Acids | | Bases | | Solvents | | | Mineral | UV | | |
| solution | Concentrated | Diluited | Concentrated | Diluited | Hexane | Benzol | Acetone | Alcohol | oil | rays |
| Resistant | L <mark>imite</mark> d resistance | Resistant | Resistant | Resistant | L <mark>imite</mark> d resistance | Not resistant | Not resistant | L <mark>imited</mark> resistance | L <mark>imited</mark> resistance | L <mark>imite</mark> d resistance |

DIMENSIONAL



TECHNICAL SYMBOLOGY





IK08





STANDARDS/APPROVALS





GEWISS S.p.A. Via A. Volta, 1 24069 Cenate Sotto - Bergamo - Italy tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com sat@gewiss.com Last update 22/07/2021 Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice