



### Main

Circuit breaker application	Distribution
Range of product	C60
Product or component type	Circuit breaker
Device short name	C60 UL1077
Poles description	2P
Number of protected poles	1
Neutral position	Left
[In] rated current	16 A at 30 °C
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	D
Breaking capacity	6 kA Icu conforming to IEC 60947-2 - 440 V AC 10 kA Icu conforming to IEC 60947-2 - 125 V DC 10 kA AIR conforming to UL 1077 - 240 V AC 10 kA AIR conforming to UL 1077 - 65 V DC 5 kA AIR conforming to UL 1077 - 480Y/277 V AC 10 kA Icu conforming to IEC 60947-2 - 415 V AC 20 kA Icu conforming to IEC 60947-2 - 240 V AC
Suitability for isolation	Yes conforming to IEC 60947-2

### Complementary

[Ue] rated operational voltage	480Y/277 V AC
Magnetic tripping limit	10...14 x In
Contact position indicator	Yes
Control type	Operating handle
Local signalling	Positive break indication
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	4
Height	81 mm
Width	36 mm
Depth	78.5 mm
Product weight	0.22 kg
Colour	Grey
Mechanical durability	20000 cycles
Connections - terminals	Tunnel type terminals 2.5...25 mm <sup>2</sup> max
Tightening torque	2.5 N.m

### Environment

Standards	CSA C22.2 No 235-04 IEC 60947-2 UL 1077
IP degree of protection	IP40 conforming to IEC 60529
Tropicalisation	2
Relative humidity	95 % 55 °C
Operating altitude	2000 m
Ambient air temperature for operation	-30...70 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ambient air temperature for storage

-40...80 °C

---

## Offer Sustainability

---

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0629 - Schneider Electric declaration of conformity
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

---