



PG THREADS

PART No.	THREAD A	NOMINAL DIMENSIONS (mm)				NOMINAL CONDUIT ØF
		B	C	D	E	
SP10/PG7/A	PG7	8.0	5.5	23.0	14.0	10.0
SP12/PG9/A	PG9	8.0	8.5	23.0	17.0	14.0
SP16/PG11/A	PG11	10.0	11.5	25.5	20.0	17.0
SP20/PG16/A	PG16	12.0	15.3	29.0	24.0	21.0
SP25/PG21/A	PG21	12.0	19.0	36.5	30.0	26.0
SP32/PG29/A	PG29	14.0	26.2	39.0	38.0	34.0
SP40/PG36/A	PG36	15.0	34.2	43.0	50.0	44.5
SP50/PG42/A	PG42	15.0	45.0	45.0	66.5	55.0
SP63/PG48/A	PG48	20.0	54.0	57.0	76.5	64.5



BIRMINGHAM ENGLAND

This drawing/document is a COPYRIGHT and the property ADAPTAFLEX LIMITED it must not be copied (in whole or part) used for manufacture or otherwise disclosed without prior written consent of the company. The Company's policy is one of continuous improvement and it therefore reserves the right to change specifications at any time without notice.

MATERIAL BRASS

FINISH NICKEL PLATE

COLOUR

DATE 12/6/2000

CHARTS 049

TITLE

SP;SN;LFH-SP
A-TYPE
FITTING