



PG THREADS

PART No.	THREAD A	NOMINAL DIMENSIONS (mm)					NOMINAL CONDUIT ϕG
		B	C	D	E	F	
S10/PG7/B	PG7	8.0	4.1	14.0	14.0	29.0	10.0
S12/PG9/B	PG9	7.8	7.5	17.0	16.8	29.5	14.0
S16/PG11/B	PG11	9.0	10.2	20.0	20.0	32.4	17.0
S20/PG16/B	PG16	10.0	14.5	24.0	24.0	33.9	21.0
S25/PG21/B	PG21	12.0	16.9	30.0	30.0	46.0	26.0
S32/PG29/B	PG29	14.0	24.1	38.0	38.0	47.0	34.0
S40/PG36/B	PG36	15.0	30.8	50.0	50.0	55.7	44.5
S50/PG42/B	PG42	15.0	42.5	66.5	66.5	57.9	55.0



BIRMINGHAM ENGLAND

This drawing/document is a COPYRIGHT and the property ADAPTAFLEX LIMITED it must not be copied (in whole or part) used for manufacture or otherwise disclosed without prior written consent of the company. The Company's policy is one of continuous improvement and it therefore reserves the right to change specifications at any time without notice.

MATERIAL **BRASS**

FINISH **NICKEL PLATE**

COLOUR

DATE **08/08/05**

CHARTS 151

TITLE

**S/SS
B-TYPE
FITTING**