



FITTING – SUPPLIED WITH LOCKNUT

PART No.	NOMINAL CONDUIT	THREAD	MIN. BORE	NUT DIA.	THREAD LENGTH	NOMINAL LENGTH
XF12/M16/D	12	M16x1.5	8	22	11.5	35.5
XF16/M16/D	16	M16x1.5	10	27	11.5	35.5
XF16/M20/D	16	M20x1.5	10	27	13	37
XF20/M20/D	20	M20x1.5	13.5	33	13	43.5
XF25/M25/D	25	M25x1.5	19	43	15.5	52.5
XF32/M32/D	32	M32x1.5	25	47	16.5	53.5
XF40/M40/D	40	M40x1.5	32	56	18	58
XF50/M50/D	50	M50x1.5	38	62	20	60



BIRMINGHAM ENGLAND

This drawing/document is a COPYRIGHT and the property ADAPTAFLEX LIMITED It must not be copied (in whole or part) used for manufacture or otherwise disclosed without prior written consent of the company. The Company's policy is one of continuous improvement and it therefore reserves the right to change specifications at any time without notice.

MATERIAL **NYLON 66**

FINISH **FINE SPARK**

COLOUR **BLACK**

DATE **31/1/06**

CHARTS 161

TITLE

**DIMENSIONS METRIC
FITTING TYPE XF/D**