

**APPLICABLE PRODUCTS: MG-TAP**

Part code	Colour	RAL/Pantone
47090N, 47091N, 47092N, 47093N, 47094, 47096, 47097, 47790, 47791	White	-
47040N, 47041N, 47042N, 47043N	Yellow	-
47000, 47001, 47002, 47003, 47004, 47094, 47006, 47096, 47007, 47097, 47790, 47791, 4700, 47701	Metallic grey	-

**TECHNICAL CHARACTERISTICS**

Criterion	Detail
Material type	Polyvinylchloride (PVC)
Material self-extinguishing class	Class V0 (UL 94)
Material Halogen free	NO
Adhesive type	-----
Adhesive application temperature range (°C)	-----
Adhesive adhesion on Stainless Steel (N/m)	-----
Total thickness of medium (mm)	0,50
Medium operating temperature range (°C)	-30 ÷ +80
RoHS compliant	YES

**TEST DATA**

Reference	Scope	Result
UNI EN ISO 4892-2	UV resistance (Standard test 500 h)	Compliant
CEI 16-7	Thermal resistance	Compliant
CEI 16-7	Print integrity	Compliant
IEC 61439-1:2009 clause 10.2.7	Print integrity	Compliant
CEI 23-11 (CEI EN 61058-1)	Print integrity	Compliant
CEI EN 61010-1 (VDE 0411-1)	Print integrity	Compliant
CEMBRE internal standard (alcohol applied)	Print integrity	Compliant

NOTES: Test media were printed with original Cembre ribbons on Cembre printing systems.

Rev.	Date	Purpose of revision	Compiled by	Verified by	Approved by
0.0	11/12/2009	First version	F. Bortot	A. Seno	E. Peroni

**CEMBRE SpA reserves the right to modify and improve products without notice.**

This data sheet is an accurate translation of the original.