

**IDENTIFICATION & LABELLING SYSTEMS
DATA SHEET****PDS 0052****APPLICABLE PRODUCTS: Transparent holders****Part code***PM, PMF, PMFT, PM-ET, PM-DT, PMT-ET, PMT-DT, PM-L***TECHNICAL CHARACTERISTICS**

Criterion	Detail
<i>Material type</i>	<i>PVC compound (Lead free)</i>
<i>Material self-extinguishing class</i>	<i>Class V0 (UL 94)</i>
<i>Material Halogen free</i>	<i>NO</i>
<i>Processing method</i>	<i>Extrusion</i>
<i>Medium operating temperature range (°C)</i>	<i>-40 ÷ +90</i>
<i>RoHS compliant</i>	<i>YES</i>

TYPICAL PROPERTIES	TEST METHOD	RESULT
<i>Density (g/cm³)</i>	<i>ISO 1183</i>	<i>1,27</i>
<i>Hardness to 15" (Shore A)</i>	<i>ISO 868</i>	<i>83</i>
<i>Tensile strength (N/mm²)</i>	<i>ISO 527</i>	<i>19</i>
<i>Elongation at break (%)</i>	<i>ISO 527</i>	<i>280</i>
<i>Vicat softening point (5 Kg)</i>	<i>ISO 527</i>	<i>83,5 °C</i>
<i>Melting point</i>	<i>-----</i>	<i>189 °F</i>

TEST DATA

Reference	Scope	Result
<i>UNI EN ISO 4892-2</i>	<i>UV resistance (Standard test 500 h)</i>	<i>Compliant</i>
<i>CEI 16-7</i>	<i>Thermal resistance</i>	<i>Compliant</i>

NOTES: *Does not apply.*

<i>Rev.</i>	<i>Date</i>	<i>Purpose of revision</i>	<i>Compiled by</i>	<i>Verified by</i>	<i>Approved by</i>
<i>0.0</i>			<i>F. Bortot</i>		

CEMBRE SpA reserves the right to modify and improve products without notice.

This data sheet is an accurate translation of the original.