

# EKSS14084

STAINLESS STEEL COMPACT VERSION, SINGLE DOOR ENCLOSURE.



H	1400
W	800
D	400
h	1294
w	694
Weight (kg)	85
Part No.	EKSS14084
EAN	8713574191822



IP 66, NEMA 4x, 12, 13 IK10

Innovative improved design, the Multi-K stainless steel range is designed with cleanliness and ingress protection in mind. The sturdy construction, with the 25mm hole pattern, one piece body and removable rear panel, ensures superior rigidity and easy access. Fully compatible with MultiFlex range of accessories, the EKSS range is the ideal solution for food and chemical industries, outdoor applications and marine environments.

**Material:** AISI 304 pre-grained stainless steel / AISI 316L

**Body and removable rear panel:** 1.5mm. Door:

**2mm. Bottom Plates:** 1.5mm.

**Mounting plate:** 2.7mm galvanized steel.

**Body:** One piece enclosure body. Integrated depth profiles with hole pattern allowing mounting plate adjustable in depth.

**Door:** Surface mounted with 4 hinges allowing left or right hand opening. Including door frame with 25mm hole pattern and earthing studs.

**Rear panel:** Fitted by M6 torx screws. Standard facilities for rear door mounting.

**Lock:** External espagnolette 4-point locking system. Standard fitted double-bit 3mm insert. It can be exchanged for the standard range of inserts, Euro-cylinder and swing handle.

**Bottom plates:** One piece bottom plate with injected polyurethane gasket to ensure maximum sealing.

**Mounting plate:** Double folded and slides into position. Adjustable in depth by steps of 25mm.

**Mounting plate is delivered attached on the outside of the enclosure packaging.**

**Earthing:** Door is equipped with separate welded earthing studs and earthing to the frame can be accomplished by using the ECF.

**Finish:** 240s pre-grained stainless steel (0.5 microns average).

**Protection:** Complies with IP 66, Nema 4x, 12 & 13. IK10.

**Delivery:** One piece body with fitted door, bottom plates and mounting plate, including door earthing studs. Delivered on a pallet with width identical to the enclosure to allow installing of equipment without removal. Mounting plate is attached to the outside of the enclosure packaging. All the packing material is recyclable.