MCD22126R5

MILD STEEL COMBINABLE VERSION, DOUBLE DOOR ENCLOSURE

















IP 55, NEMA 12, 13 IK 10

With a reliable design, the MCD range of mild steel double door floor standing enclosures combines strength and practicality in one. Infinite mounting possibilities and a complete range of accessories means you can rely on the MCD to get the job done.

With mounting plate

Н	2200
W	1200
D	600
h	2094
w	1094
d	559
W (c)	1032
D (c)	710
Weight (kg)	214
Part No.	MCD22126R5
EAN	8713574129535

Material: Frame:1.5/1.75mm painted steel. Doors: 2mm painted steel. Rear, roof and side panels: 1.35mm painted steel. Mounting plate: 2.7mm galvanized steel. Bottom plates: 1mm galvanized steel.

Frame: Seam welded reversed open profiles with 25mm hole pattern according to DIN 43660. Including integrated external hole pattern.

Door: Mounted with four hinges. Including door frame with 25mm hole pattern. Doors cannot be reversed. Separate doors to be ordered for left hand door locking.

Rear panel: Fitted by M6 torx screws. Standard facilities for rear door mounting. Split rear panels in 1600 wide enclosures.

Side panels: Supplied as an accessory.

Roof panel: Removable.

Lock: Espagnolette 4-point locking system. Does not interfere with the enclosure inner space. Standard double-bit lock with 3mm pin. Can be exchanged for standard inserts or Euro-cylinder and swing handle.

Bottom plates: Consists of three or four (D>600) pieces.

Mounting plate: Double folded and adjustable in depth by steps of 25mm with the MPD02 accessory. Fitted inside for 1600 wide enclosures.

Earthing: All panels are earthed through their fittings and equipped with a separate earthing stud.

Finish: RAL 7035 structured powder coating.

Protection: Corresponds with IP 55, Nema 12 & 13. IK 10.

Mounting requirement: Standard delivery ready for combined installation. For stand-alone installation add side panels.

Delivery: Frame with fitted doors, rear panel, roof panel, bottom plates, mounting plate and door frame. Delivery also includes earthing bolts. Delivered on a pallet with identical width of the enclosure to allow suiting without removal. Packing material is recyclable.

