

MCSS18085

STAINLESS STEEL COMBINABLE VERSION, SINGLE DOOR ENCLOSURE.



H	1800
W	800
D	500
h	1694
w	694
Weight (kg)	117
Part No.	MCSS18085
EAN	8713574191662



IP 56, NEMA 12, 13 IK10

Multi-Flex range of stainless steel single door floor standing enclosures sets new standards when it comes to strength and ease of use. The sturdy construction of the Eldon MCSS range, with its 1.5mm thick stainless steel profile frame and 25mm hole pattern in all directions, provides high corrosion resistance and rigidity. Intended for harsh environments, can be used as a stand alone system or suited together by the use of baying brackets.

Material: AISI 304 pre-grained stainless steel / AISI 316L

Frame: 1.5mm. Door: 2 mm . Rear, roof and side panels: 1.5mm. Bottom plates: 1.5mm stainless steel. Mounting plate: 2.7mm galvanized steel.

Frame: Seam welded reversed open profiles with 25mm hole pattern according to DIN 43660.

Door: Mounted with four hinges allowing left or right hand opening. Including door frame with 25mm hole pattern.

Rear panel: Fitted by M6 torx screws. Standard facilities for rear door mounting.

Side panels: Supplied as an accessory.

Roof panel: Removable.

Lock: Espagnolette 4-point locking system. Does not interfere with the enclosure inner space. Standard double-bit 3mm lock. Can be exchanged for standard inserts or Euro-cylinder and swing handle.

Bottom plates: One piece bottom plate with injected polyurethane gasket to ensure maximum sealing.

Mounting plate: Double folded and slides into position. Adjustable in depth by steps of 25mm with the MPD02 accessory. Mounting plate is delivered attached on the outside of the enclosure packaging.

Earthing: All panels are earthed through their fittings and are equipped with a separate earthing stud.

Finish: 240s pre-grained stainless steel (0.5 microns average).

Protection: Corresponds with IP 56, NEMA 12 and 13. IK10.

Delivery: Frame with fitted door, rear panel, roof panel, bottom plates, mounting plate and door frame. Delivery also includes earthing bolts. Delivered on a pallet with identical width of the enclosure to allow suiting without removal. All packing material is recyclable. mounting plate is on the outside.

Mounting requirement: Standard delivery ready for combined installation. For stand-alone installation add side panels.