

MKD18124R5

MILD STEEL COMPACT VERSION, DOUBLE DOOR



With mounting plate

H	1800
W	1200
D	400
h	1694
w	1094
d	359
W (c)	1032
D (c)	310
Weight (kg)	175
Part No.	MKD18124R5
EAN	8713574126572

Material: Body, rear and roof panels: 1.35mm painted steel. Door: 2mm painted steel. Mounting plate: 2.7mm galvanized steel. Bottom plates: 1mm galvanized steel.

Body: Four times folded and seam-welded frame. Integrated double row hole pattern.

Door: Mounted with four hinges. Including door frame with 25mm hole pattern. Standard doors cannot be reversed. Separate doors to be ordered for left hand door locking.

Rear panel: Fitted by M6 torx screws. Standard facilities for rear door mounting. Split rear panels on 1600mm wide enclosures.

Roof panel: Removable

Lock: External espagnolette 4-point locking system. Standard fitted double-bit lock with 3mm pin. Can be exchanged for standard inserts or Euro-cylinder and swing handle.

Bottom plates: Consists of three pieces.

Mounting plate: Double folded and adjustable in depth by steps of 25mm with the MPD02 accessory. Supplied outside of the enclosure packaging. Fitted inside for 1600mm enclosures.

Earthing: All panels are earthed through their fittings and are equipped with a separate earthing stud.

Finish: RAL 7035 structured powder coating.

Protection: Complies with IP 55 and Nema 12, 13. IK 10.

Delivery: Enclosure with fitted door, roof panel, rear panel, bottom plates, mounting plate and door mounting frame. Delivery also includes earthing bolts. The enclosure is delivered on a pallet identical to the enclosure width. All packing material is recyclable.



IP 55, NEMA 12, 13. IK 10

As the double door version to MKS, the MKD offers the same innovative design and strength as its smaller brother. With a removable rear and roof panel to allow easy hole punching. The MKD maintains IP 55, and the rear panels can be changed for additional doors.