

# MKS16104R5

MILD STEEL COMPACT VERSION, SINGLE DOOR



## With mounting plate

H	1600
W	1000
D	400
h	1494
w	894
d	359
W (c)	832
D (c)	310
Weight (kg)	131
Part No.	MKS16104R5
EAN	8713574127951

**Material:** Body, rear and roof panels : 1.35mm painted steel. Door: 2mm painted steel. Mounting plate: 2.7mm galvanized steel. Bottom plates: 1mm galvanized steel.

**Body:** Four times folded and seam-welded frame. Integrated double row hole pattern.

**Door:** Mounted with hinges allowing left or right hand opening. Including door frame with 25mm hole pattern.

**Rear panel:** Fitted by M6 torx screws. Standard facilities for rear door mounting.

**Roof panel:** Removable

**Lock:** External espagnolette 4-point locking system. Standard fitted double-bit lock with 3mm pin. Can be exchanged for standard inserts or Euro-cylinder and swing handle.

**Bottom plates:** Consists of three pieces.

**Mounting plate:** Double folded and slides into position. Adjustable in depth by steps of 25mm with the MPD02 accessory. Supplied outside of the enclosure packaging.

**Earthing:** All panels are earthed through their fittings and are equipped with a separate earthing stud.

**Finish:** RAL 7035 structured powder coating.

**Protection:** Complies with IP 56 and Nema 4, 12, 13, IK 10. \* To achieve IP 66, use gasket kit BG01.

**Delivery:** Body with fitted door, rear panel, roof panel, bottom plates, mounting plate and door frame. Delivery also includes earthing bolts. Delivered on a pallet with width identical with the enclosure. All packing material is recyclable.



IP 66, NEMA 4, 12, 13, IK 10

Ergonomic and strongly designed, the MultiFlex range of mild steel single door floor standing enclosures offers any user maximum reliability. With a removable rear and roof panel to allow easy hole punching and hinges for left or right hand opening, MKS satisfies the toughest of demands.