

TLC87035

COMPACT DESIGN LIGHT



Colour RAL7035

| | |
|----------|---------------|
| Weight | 400gr |
| Part No. | TLC87035 |
| EAN | 8713574166691 |

Description: It's compact design makes it suitable for mounting in almost any enclosure or rack. Supplied including three integrated fixing methods e.g. magnet, screw and snap-in and a connection cable. Provided with a protection cap, electronic quick start and 3-way switch (on/off, door switch, permanent light). An integrated socket permits operation by an optional door switch.

Operating voltage: 100 - 240 V AC $\pm 10\%$ at 50/60Hz

Power: 8W, Current: 110V AC: 0,083 - 0,149A, 240V AC: 0,045 - 0,088A

Connection: including 2-pole 0.75mm² connection cable 2,5A length 150 cm with open end (2x 0.75mm²)

Housing: material PC-ABS-V0 (Halogen-free) Light cover: material PMMA Screw fixing: 455 - 475mm (retractable feet)

Lamp: Fluorescent lamp T5, 450 lm

Protection: IP 20/II (all insulated)

Switch: Integrated, on/off/door operated switch mode

Approvals: CE, ENEC, UR (pending)

Dimension: TLC 448 x 54,5 x 26mm TLCF 485 x 5 x 44mm
Also suitable for 19" mounting on the 19" profiles, only 1U high

Accessories: Design frame, TLCF (without mounting material), door switch cable, TLCS and door switch, DSW01 to be ordered separately.

Pack quantity: Light with integrated magnet, screw and click-in fixing, with mounting material and power cable (L=150cm).

