

UCP540

UNIPLAST ENCLOSURE COMPACT VERSION



Plain door

H	515
W	415
D	230
Weight (kg)	6.58
N° of locking points	3
Part No.	UCP540
EAN	8713574099975

Material: Fibre-glass reinforced polyester.
UCPT viewing area: polycarbonate.

Body: Monoblock moulded 3mm thick. Four holes for direct wall fixing. Without gland plate openings.

Door: Door with or without window and 180° opening. For UCP/UCPT750 and above a door support is supplied for easier closing. Sealing is by an injected one piece polyurethane gasket.

Lock: Double-bit 3mm insert and 90° movement. UCP/UCPT540 and above have three locking points. Other locks are available as an accessory.

Temperature resistance: -50°C to 70°C in continuous use (peak temperatures up to 150°C).

Characteristics: Self extinguishing and halogen free. Double isolated according to EN60439-1. Rated insulation voltage $U_i=1000V$.

Protection: Complies with IP 66 and NEMA 4, 4X, 12 and 13. Impact resistance IK 10 (IK 07 for enclosures with transparent door)

Finish: RAL 7035, precoloured raw material.

Delivery: Enclosure with door, fixing screws for the mounting plate and a self adhesive rain strip.

Approvals: CE. For CSA and UL approvals, please contact our sales department.



IP66 / NEMA 4, 4X, 12, 13 | IK10 / IK07

The Uniplast range of Compact polyester enclosures, conforms to IP 66. Uniplast Compact is a fibre-glass reinforced polyester design, and is double insulated to give maximum safety to users. A large range of standard sizes and numerous mounting possibilities makes Uniplast Compact extremely flexible.