

(E @

IP65, IP54

The Uniplast range of Modular polyester enclosures, conforms to IP65 for single door enclosures and IP54 for double door enclosures. Uniplast Modular is a fibre-glass reinforced polyester design, and is double insulated to give maximum safety to users. Different modular enclosures can be joined together to achieve larger configurations.

Material: Fibre-glass reinforced polyester. UDPT viewing area: polycarbonate.

Body: Modular moulded, with rear fixing holes. Direct fixing to the wall or by use of wallmounting brackets, to a pole by use of UPM or to the floor by use of the plinth UPP or DIN-base UAF and UMPS. In single plain door enclosures, sealing is ensured by an EPDM CR gasket glued against the frame.

Door: Flush mounted door with or without window and 100° opening. For larger sizes a door support is supplied for easier closing. In double door enclosures, sealing is ensured by an injected one piece polyurethane gasket.

Lock: Premounted handle suitable for all types of half cylinder locks (standard depth of 40mm). Five locking points (three points in 500mm width enclosures)

Temperature resistance: -50°C to 70°C in continuous use (peak temperatures up to 150°C).

Characteristics: Self extinguishing and halogen free. Double isolated according to EN60439-1. Rated insulation voltage Ui=1000V.

Protection: Complies with IP65 for single door enclosures and IP54 for double door enclosures. Impact resistance IK 08 (IK 07 for enclosures with transparent door).

Finish: RAL 7035, precoloured raw material.

Delivery: Enclosure with door, fixing screws for the mounting plate and wallmounting brackets.(Lock cylinder is not included in the delivery)

Approvals: CE. For CSA and UL approvals, please contact our sales department.



UDP/UDPT

UNIPLAST ENCLOSURE MODULAR VERSION

Plain door

н	w	D	Weight (kg)	N° of doors	N° of doors	Part No.
500	500	320	16	1	1	UDP5050
500	750	320	19	1	1	UDP5075
750	500	320	20	1	1	UDP7550
750	750	320	25	1	1	UDP7575
750	1000	320	30	1	1	UDP75100
н	w	D	Weight (kg)	N° of doors	N° of doors	Part No.
750	500+750	320	38	2	2	UDP75125N
Plain door						
н	w	D	Weight (kg)	N° of doors	N° of doors	Part No.
1000	500	320	25	1	1	UDP10050
1000	750	320	30	1	1	UDP10075
1000	1000	320	36	1	1	UDP100100



UDP/UDPT UNIPLAST ENCLOSURE MODULAR VERSION

	500	750	1000	1250
500	I			
750				
1000	I	1		
1250		1		

