

sealing washers

neoprene and fibre face sealing washers



metric thread
part number

metric thread
part number

PG thread
part number

PG thread
part number

| | | | |
|------|------|--------|--------|
| SW12 | FW12 | SWPG7 | FWPG7 |
| SW16 | FW16 | SWPG9 | FWPG9 |
| SW20 | FW20 | SWPG11 | FWPG11 |
| SW25 | FW25 | SWPG13 | FWPG13 |
| SW32 | FW32 | SWPG16 | FWPG16 |
| SW40 | FW40 | SWPG21 | FWPG21 |
| SW50 | FW50 | SWPG29 | FWPG29 |
| SW63 | FW63 | SWPG36 | FWPG36 |
| | | SWPG42 | |
| | | SWPG48 | FWPG48 |

earthing washers

shake proof washer

earth tag washer



metric thread
part number



metric thread
part number

| | |
|-------|--------|
| SPW16 | |
| SPW20 | ET-M20 |
| SPW25 | ET-M25 |
| SPW32 | |

fixing clips

plated steel with black pvc liner or stainless steel.

LFH liner available on request



to fit conduit size

part number

part number

| | | |
|----|-------|-----------|
| 10 | FCC10 | FCC10-SS* |
| 12 | FCC12 | FCC12-SS* |
| 16 | FCC16 | FCC16-SS |
| 20 | FCC20 | FCC20-SS |
| 25 | FCC25 | FCC25-SS |
| 32 | FCC32 | FCC32-SS |
| 40 | FCC40 | FCC40-SS |
| 50 | FCC50 | FCC50-SS* |
| 63 | FCC63 | |
| 75 | FCC75 | |

conduit clip

NEW

nylon conduit clip with integral lid - black or grey



conduit clip for
corrugated

conduit clip for
plain or rigid

| | |
|-------|----------|
| FCL10 | |
| FCL13 | |
| FCL16 | FCL16B-P |
| FCL20 | FCL20B-P |
| FCL25 | FCL25B-P |
| FCL34 | FCL33B-P |
| FCL42 | |
| FCL54 | |

cable glands

NEW

Our range of Cable glands provides an easy to assemble, fast fit, liquid tight solution for multipurpose applications.

Available in four colours, Black, Red (RAL 3020), White and Light Grey (RAL 7035) they have been designed to provide the highest degree of functionality and safety.



| Thread Size | Black Part No. | Red Part No. | White Part No. | Grey Part No. | Thread Length (mm) | Cable Dia (min) (mm) | Cable Dia (max) (mm) | Spanner Size (mm) | Pack Quantity |
|-------------|----------------|--------------|----------------|---------------|--------------------|----------------------|----------------------|-------------------|---------------|
| M16 | CGM16B | CGM16R | CGM16W | CGM16G | 11 | 5 | 10 | 22 | 100 |
| M20 | CGM20SB | CGM20SR | CGM20SW | CGM20SG | 11 | 6 | 12 | 24 | 100 |
| M20 | CGM20B | CGM20R | CGM20W | CGM20G | 11 | 10 | 14 | 27 | 100 |
| M25 | CGM25B | CGM25R | CGM25W | CGM25G | 11 | 13 | 18 | 33 | 50 |
| M32 | CGM32B | | | | 11 | 18 | 25 | 41 | 25 |

Red, white and grey supplied with locknut. Black supplied without locknut.



| Thread Size | Nickel plated brass | Thread Length (mm) | Cable Dia (min) (mm) | Cable Dia (max) (mm) | Spanner Size (mm) | Pack Quantity |
|-------------|---------------------|--------------------|----------------------|----------------------|-------------------|---------------|
| M16 | B-M16-CG | 12 | 4.5 | 10 | 20 | 10 |
| M20 | B-M20-CG | 12 | 7 | 13 | 24 | 10 |
| M25 | B-M25-CG | 12 | 9 | 17 | 29 | 10 |
| M32 | B-M32-CG | 15 | 11 | 21 | 36 | 2 |
| M40 | B-M40-CG | 15 | 19 | 28 | 45 | 2 |
| M50 | B-M50-CG | 15 | 27 | 35 | 54 | 1 |

Technical Details

- Material: PA6
- IP Rating; IP68 (4 bar)
- Nitrile Rubber seal
- Produced and tested in accordance with EN 50262:1999
- Temperature range; -20°C to +90°C

Technical Details

- Material: Nickel plated brass
- IP Rating; IP68 (10bar) + IP69K
- Produced and tested in accordance with EN 50262:1999
- Temperature range; -40°C to +100°C (static)
-20°C to +100°C (dynamic)
- UL Listed

available on request: EMC versions, short threaded, Reduced clamp range.

STANDARDS



* refer to technical details